

CHEMIKO GUARD ACF

Acrylic Based Crack Filler

1/1/2 017



DESCRIPTION

CHEMIKO GUARD ACF is composed of high quality, weather durable acrylic emulsion polymer, graded fillers, light fast pigment & additives. It is a single pack, ready to use flexible component for filling cracks in plastered surfaces because of its excellent bonding, ease of application, water resistance, aesthetic appearance & durability.

ADVANTAGES/CHARACTERISTICS

- Excellent bonding
- Water resistant
- Durable and Flexible
- Easy to Apply
- Ready to use

APPLICATION INSTRUCTIONS

- Surface must be free from dust, oil, grease, and loose particles etc.
- Moisten the surface before applying CHEMIKO GUARD ACF Paste.
- Fine hair line cracks must be widened up to 1 mm minimum using a scrapper and then filled.
- For filling CHEMIKO GUARD ACF Paste on the internal surface, existing POP or putty must be removed till plaster surface is exposed.
- Fill CHEMIKO GUARD ACF Paste when the surface is tacky and not dried completely.

FIELD OF APPLICATION/USES

- To level the undulation of the unplastered or plastered ceilings and walls before painting.
- To provide smooth finish to brick, stone, and wood works. As an excellent sculpting material

TECHNICAL DATA

Properties	Requirement
Appearance	Thick paste
Viscosity (Spindle No: 7; RPM : 10 @ 25° C)	10000 ± 2000 cps
static cracks Bridge	Upto 3mm to 5mm
Solid %	82 ± 5
Dry view	Flexible
Primer Mix proportion	1:1
Coverage	25-30RM/kg for 5mm
Durability	Good
Color	Off White

DISCLAIMER

The above information and details herein are based on the tests conducted & experience on application and usage. The user is advised to carry out the test and take trials to satisfy on the suitability of the products and meeting his requirement considering the prevailing conditions prior to apply/ using it on larger area. As the conditions under which the products are used or transported are beyond our control. We would not hold ourselves responsible on its consequential nonperformance.

CHEMIKO GUARD ACF

Acrylic Based Crack Filler

1/1/2 017



Application

- Press CHEMIKO GUARD ACF Paste firmly into the crack with a spatula or putty knife and level with the surface.
- Care must be taken to avoid formation of cavities or bubbles during application.
- Allow it to set for 24 hours and then apply another coat of CHEMIKO GUARD ACF Paste.
- Further POP or putty application can be taken up once it is fully dry.
- For best results allow CHEMIKO GUARD ACF Paste to cure for 7 days.

HEALTH & SAFETY

- Cementitious mortars & slurries modified with when mixed or when become damp, may release alkali which can be harmful to skin & eye.
- Wear suitable protective clothing, gloves, eye protection and respiratory protective equipment during application. In case of contact with skin, with eyes, rinse with plenty of clean water and then cleanse with soap water.
- Keep out of reach of children

STORAGE AND SHELF LIFE

- Shelf life is 12 months from the date of manufacturing.
- Store in a cool & dry place in unopened condition (Prevent from direct sunlight).

AVAILABLE PACKING: 0.5KG and 1KG

DISCLAIMER The above information and details herein are based on the tests conducted & experience on application and usage. The user is advised to carry out the test and take trials to satisfy on the suitability of the products and meeting his requirement considering the prevailing conditions prior to apply/ using it on larger area. As the conditions under which the products are used or transported are beyond our control. We would not hold ourselves responsible on its consequential nonperformance.

